

SEPT 28, 1991

AIBENHART SKI CLUB

PG 2

HEATER MUST BE PROTECTED AGAINST
FOOT TRAVEL AND DAMAGE FROM
OTHER CAUSES.

A COVER SHOULD BE PROVIDED ON
THE MAIN CIRCUIT BREAKER BOX AND
ON ANY OTHER JUNCTION BOXES WHERE
COVERS MAY BE MISSING.

THERE IS SOME 'BX' TYPE ELECTRICAL
CABLE APPARENTLY STILL IN USE.
THIS APPEARS TO BE SOMEWHAT
CORRODED DUE TO THE WAMP CONDITIONS
IN THE BASEMENT. ANY BX STILL IN
USE SHOULD BE REPLACED. ANY WIRES
WHICH ARE OR MAY BE ABANDONED
SHOULD BE REMOVED. ANY HANGING
WIRES SHOULD BE SECURED.

A BASIC LIFE SAFETY REQUIREMENT
IS FOR A SMOKE DETECTION SYSTEM.
CODE REQUIRES A HARD WIRED SMOKE
DETECTOR IN EACH SLEEPING ROOM.

ALSO A DETECTOR SYSTEM IS
REQUIRED IN CORRIDORS, STAIRWAYS
AND ROUTES OF EGRESS FROM THE
BUILDING. A DETECTOR IS REQUIRED
IN THE BASEMENT. ALTHOUGH NOT
REQUIRED BY CODE, A DETECTOR IS
RECOMMENDED IN THE ATTIC.

THE SYSTEM IN THE STAIRWAYS,
CORRIDORS ETC. MUST BE SO ARRANGED
THAT THE ACTIVATION OF ANYONE OF
ITS DETECTORS WILL CAUSE AN ALARM
THROUGHOUT THE BUILDING SUFFICIENT
TO AWAKEN ANY SLEEPERS.

THE INDIVIDUAL DETECTORS IN THE
SLEEPING ROOMS ARE NOT REQUIRED
TO BE ON THIS SYSTEM BUT DUE
TO THE CONFIGURATION OF THE ROOMS
ON THE SECOND FLOOR WITH ESCAPE